10697 714

Freeform Search

Database:	US Pre-Grant Publication Full-Text Database US Patents Full-Text Database US OCR Full-Text Database EPO Abstracts Database JPO Abstracts Database Derwent World Patents Index IBM Technical Disclosure Bulletins			
Term:	L14 and "calibration"			
Display:	10 Documents in Display Format: - Starting with Number 1			
Generate: O Hit List @ Hit Count O Side by Side O Image				
Search Clear Interrupt				
Search History				

DATE: Tuesday, July 20, 2004 Printable Copy Create Case

Set Name side by side		Hit Count	Set Name result set
DB=PG	PB, $USPT$, $USOC$, $EPAB$, $JPAB$, $DWPI$, $TDBD$; $PLUR = YE$	S; OP=ADJ	
<u>L17</u>	L15 and "sensor fault"	0	<u>L17</u>
<u>L16</u>	L15 and "sensor failure"	22	<u>L16</u>
<u>L15</u>	L14 and "calibration"	433	<u>L15</u>
<u>L14</u>	374/1	818	<u>L14</u>
<u>L13</u>	two serially connected sensors	1	<u>L13</u>
<u>L12</u> -	two serially connected-thermistors-	2	— <u>L12</u> —
<u>L11</u>	two parallel thermistors	3	<u>L11</u>
<u>L10</u>	two heat sensitive resistors	12	<u>L10</u>
<u>L9</u>	two temperature sesnsitive resistors	0	<u>L9</u>
<u>L8</u>	(calibration) and (serially connected temperature)	0	<u>L8</u>
<u>L7</u>	two serially connected temperature	2	<u>L7</u>
<u>L6</u>	two heat sensitive in series	0	<u>L6</u>
<u>L5</u>	two temperature sensing in series	0	<u>L5</u>
<u>L4</u>	two parallel temperature sensing	3	<u>L4</u>
<u>L3</u>	two parallel temperature sensors	3	<u>L3</u>
<u>L2</u>	parallel temperature sensors	72	<u>L2</u>

<u>L1</u> 702/99

322 <u>L1</u>

END OF SEARCH HISTORY